

Depth Uncertainty in Neural Networks

AMLab Seminar – 10/12/2020

James Allingham & Javier Antorán

Joint Work

Javier Antorán
ja666@cam.ac.uk



**James Urquhart
Allingham**
jua23@cam.ac.uk



**José Miguel
Hernández-Lobato**
jmh233@cam.ac.uk




Uncertainty in Deep Learning...

People saying AI will
take over the world:



Meanwhile, my
Deep Neural Network:




Probabilistic Inference: A biased coin






Likelihood

$$p(\theta | \mathcal{D}) = \frac{p(\mathcal{D} | \theta)p(\theta)}{p(\mathcal{D})}$$


Prior



Different Weight Configurations yield Diverse Predictions



Weight Space Bayesian Neural Networks (BNNs)



- Predictions incorporate model uncertainty!

$$p(\mathbf{Y}^* | \mathbf{X}^*, \mathcal{D}) = \int p(\mathbf{Y}^* | \mathbf{X}^*, \theta) p(\theta | \mathcal{D}) d\theta$$


But Wait! There are 2 big issues:

How to Specify Meaningful Priors?


Samples from fully connected BNN prior converge to white noise!

$$p(\theta) = \mathcal{N}(\theta; 0, I)$$


1 Hidden Layer



5 Hidden Layer




20 Hidden Layer



The Weight Posterior is Intractable

- The model's likelihood under a BNN model is a very complex, high dimensional and multimodal function.



[Li et al.]

- **Intractable evidence:**




$$p(\mathcal{D}) = \int p(\mathcal{D} | \theta)p(\theta)d\theta$$

- **Intractable predictive:**

$$p(\mathbf{Y}^* | \mathbf{X}^*, \mathcal{D}) = \int p(\mathbf{Y}^* | \mathbf{X}^*, \theta)p(\theta | \mathcal{D})d\theta$$


- Must resort to **Approximate Inference**

Our Uncertainty Estimates are Almost Always Biased by Our Approximations




As a result: Unreliable Predictions and Uncertainty Estimates


Dropout



MFVI



Ensemble



Detailed Studies:

Foong et al. "On the expressiveness of approximate inference in bayesian neural networks." *NeurIPS* (2020).

Wenzel et al. "How Good is the Bayes Posterior in Deep Neural Networks Really?" CoRR abs/2002.02405 (2020)

Try for yourself:
[github.com/JavierAntoran/
Bayesian-Neural-Networks](https://github.com/JavierAntoran/Bayesian-Neural-Networks)

Can we Elude the Difficulties of Weight Space?

- Weight space inference is difficult:

$$p(\theta | \mathcal{D}) = \frac{p(\mathcal{D} | \theta)p(\theta)}{p(\mathcal{D})}$$



- We can generalise by explicitly considering our model class:

$$p(\theta | \mathcal{D}, \mathcal{M}) = \frac{p(\mathcal{D} | \theta, \mathcal{M})p(\theta | \mathcal{M})}{p(\mathcal{D} | \mathcal{M})}$$



- Neural Architecture Search performs MAP inference over \mathcal{M} :

$$p(\mathcal{M} | \mathcal{D}; \theta) \approx \delta(\mathcal{M} - \mathcal{M}^*);$$
$$\mathcal{M}^* = \operatorname{argmax}_{\mathcal{M}} p(\mathcal{D} | \mathcal{M}; \theta)p(\mathcal{M})$$

- We perform full inference over \mathcal{M} : $p(\mathcal{M} | \mathcal{D}; \theta) = \frac{p(\mathcal{D} | \mathcal{M}; \theta)p(\mathcal{M})}{p(\mathcal{D}; \theta)}$




DUN: Intuition




- Depth **Uncertainty Networks (DUNs)**, transform uncertainty over depth into predictive uncertainty.

It's not Intractable if its countable! (In this case)




- We perform inference over network depth (discrete space)
- Sequential computation is amortised!



$$p(y = c | \mathbf{x}^{(n)}, d = i; \theta) \\ = f_{D+1} \circ (f_i \circ f_{i-1} \dots \circ f_1)(\mathbf{x}^{(n)})$$

DUN: Inference with a Single Forward Pass



$$d \sim \text{Cat}(d; \beta)$$

$$\log p(\mathcal{D}; \boldsymbol{\theta}) = \log \sum_{i=0}^D \left(p_{\boldsymbol{\beta}}(d=i) \cdot \prod_{n=1}^N p(\mathbf{y}^{(n)} | \mathbf{x}^{(n)}, d=i; \boldsymbol{\theta}) \right)$$

$$\geq \mathcal{L}(\boldsymbol{\alpha}, \boldsymbol{\theta}) = \sum_{n=1}^N \mathbb{E}_{q_{\boldsymbol{\alpha}}(d)} \left[\log p(\mathbf{y}^{(n)} | \mathbf{x}^{(n)}, d; \boldsymbol{\theta}) \right] - \text{KL}(q_{\boldsymbol{\alpha}}(d) \| p_{\boldsymbol{\beta}}(d))$$

But Why VI? → Optimising Hyperparameters (θ) is Hard

- With the ML objective, the rich get richer and the posterior is prone to collapse

$$\frac{\partial}{\partial \boldsymbol{\theta}} \log p(\mathcal{D}; \boldsymbol{\theta}) = \sum_{i=0}^D p(d=i | \mathcal{D}; \boldsymbol{\theta}) \frac{\partial}{\partial \boldsymbol{\theta}} \log p(\mathcal{D}|d=i; \boldsymbol{\theta})$$

- With VI, the optimization of variational parameters and model weights is decoupled


$$\frac{\partial}{\partial \boldsymbol{\theta}} \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\alpha}) = \sum_{i=0}^D q_{\boldsymbol{\alpha}}(d=i) \frac{\partial}{\partial \boldsymbol{\theta}} \log p(\mathcal{D}|d=i; \boldsymbol{\theta})$$

$$\frac{\partial}{\partial \alpha_i} \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\alpha}) = \log p(\mathcal{D}|d=i; \boldsymbol{\theta}) \frac{\partial}{\partial \alpha_i} q_{\boldsymbol{\alpha}}(d=i) - (\log q_{\boldsymbol{\alpha}}(d=i) - \log p(d=i) + 1) \frac{\partial}{\partial \alpha_i} q_{\boldsymbol{\alpha}}(d=i)$$




Posterior is updated with log likelihood instead of being \propto likelihood


5 layer MLP on Concrete



ResNet-50 on Fashion MNIST




Enhance!




Toy Examples!


Dropout




MFVI









DUN



Ensemble





GP-RBF





Function Diversity in DUNs vs Ensembles



DUN ResNet




DUN MLP




Deep Ensemble



Regression (ranks across 9 UCI datasets)



DUNs are Compute Efficient – UCI Edition



What if NN shape is not constant? → Adaption Layers






Image Classification (ResNet50)





DUNs are Compute Efficient – CIFAR10 Edition




Architecture Search with DUNs


Spirals (toy data)




MNIST



Fashion-MNIST



SVHN



Connections to other work


- Over-parameterised NNs are capable of representing multiple (diverse) models of the data
 - MIMO¹
 - Diversity in predictions gives good robustness
 - Hyper-deep ensembles²

¹Havasi, Marton, et al. "Training independent subnetworks for robust prediction." *arXiv preprint arXiv:2010.06610* (2020).


²Wenzel, Florian, et al. "Hyperparameter ensembles for robustness and uncertainty quantification." *Advances in Neural Information Processing Systems* 33 (2020).

Summary

- Existing methods for estimating uncertainty in deep learning are computationally expensive and often perform poorly.
- Depth **Uncertainty Networks (DUNs)**, transform uncertainty over depth into predictive uncertainty in a single forward pass.
- **DUNs provide the best robustness vs compute time trade-off** in both classification and regression with modern architectures.



Code



github.com/cambridge-mlg/DUN